Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
L1	2	("6666881").PN.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/10/20 09:02
L6	2	("5453653").PN.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/10/20 09:14
L9	149585	(electrical adj circuit)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/10/20 10:01
L10	1157	L9 same (provid$3 near4 current)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/10/20 09:14
L11	447	L10 and ((sens$4 or measur$4) with (voltage or resistance or current))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/10/20 09:14
L12	102	L10 and (heat$3 same((sens$4 or measur$4) with (voltage or resistance or current)))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/10/20 10:03
L13	7183	((236/1c,1h,3,40) or (338/13, 20-24)).CCLS.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/10/20 09:14
L14	3567	L13 and heat$4	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/10/20 09:14

L15	2076	L14 and current	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/10/20 09:14
L16	837	L15 and ((sens$4 or measur$4) with (voltage or resistance or current))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/10/20 09:14
L17	16466	((606/1,27-31,38,41-50,108, 191-200) or (623/1.1,1.11,1.15,1. 18,1.19,1.2,1.23,11.11,900,902, 903)).CCLS.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/10/20 10:00
L18	1820	17 and (stent with ((shape near4 memory) or nitinol))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/20 10:01
L19	1174	18 and (heat$4)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/20 10:02
L20	96	19 and (current with heat$3)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/20 10:02
L21	15	20 and (heat$3 same((sens$4 or measur$4) with (voltage or resistance or current)))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/10/20 10:05
L22	1	(arrangement or circuit) and (shape or size or state or configuration with stent) and (electrical with circuit) and (heat$3 with stent) and (monitor$3 with (phase near4 change)) and (control$4 with (current or flow or electricity)) and (function with (phase with change)).clm.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	AND	ON	2005/10/20 10:09

PALM Intranet

Application Number [   ] [SEARCH]

IDS Flag Clearance for Application [10618182]

IDS Information

Content	Mailroom Date	Entry Number	IDS Review	Reviewer
M844	07-11-2003	9	☑	05-21-2004 11:21:28 ryoung
M844	03-10-2005	23	☑	03-20-2005 17:20:00 dbrooks

[UPDATE]